



ECHELON TYPE CABLE 2#18, UNSHIELDED,
7/26 UTP, BELDEN 8461 OR EQUIVALENT.

SPECIFICATIONS

APPLICATIONS	Configurable sensor node to monitor temperature, humidity, pressure and other sensor types
UNIVERSIAL INPUTS (UI)	8 UI(Analog or Digital): 0–5V, 0–10V, 4–20mA, thermistor, Low-Pass filter input conditioning
DIGITAL INPUTS (DI)	NONE
DIGITAL OUTPUT (DO)	NONE
ANALOG OUTPUT (AO)	NONE
DIMENSIONS	8.0" X 4.0" X 1.5"(204mm x 102mm x38mm)
MOUNTING	Plastic SnapTrak or SB Metal Enclosure
POWER REQUIREMENT	24Vac Center-tap 2.2VA
ENVIRONMENTAL	Operating and Storage: –40 to 75°C (–40 to 168°F), 5 to 95% RH, non-condensing
INSTALLATION TYPE	PART# 950500Q: WITHOUT ENCLOSURE PART# 961500Q: WITH ENCLOSURE PART# 962500Q: ON SNAPTRACK

--	-----	07
--	-----	06
--	-----	05
--	-----	04
--	-----	03
2014-12-13	Update Logo & Adress	02
2011-12-19	Modification on DATA Description	01
DATE	DESCRIPTION	REV.

SYSTEM :
REFRIGERATION

AUTOMATISATION / CONTROL :



Micro Thermo Technologies™

12855 Rue Brault, Mirabel
Quebec, Canada, J7J 0C4
Tel: (450) 668-3033
Fax: (450) 668-2695

TITLE:
MT-500

PART# :
9XX-500Q

Drawn By :	Designed By :	Approved By :	Revision :
G.Q.	L.M.	A.H.	02
Scale :	Date :	File Name :	
N.T.S	2004-08-24	C-001 MT-500-CON	